

COMPACT PRINTER ALLOWS YOU TO MAKE A *BIG* *IMPACT*

The opportunities are endless
imagePROGRAF iPF6400SE



Everything about the imagePROGRAF iPF6400SE is designed to ensure that it fits into the smallest of spaces. A tiny footprint, complete front-loading system and output collected from the basket, the iPF6400SE is suitable for the cosiest of environments.

The iPF6400SE allows your business to bring your ideas to life, with ease.

Designed ultimately for poster printing, the iPF6400SE is packaged with our powerful PosterArtist Lite* software. A solution that allows you to, quickly and easily, produce a wide range of posters for various purposes, in four easy steps.

The iPF6400SE makes full use of Canon's unique LUCIA-EX ink system. An ink type with proven strengths in colour reproduction.

As well as the standard Cyan, Magenta, Yellow and Black configuration, the iPF6400SE utilises a Matte Black and a vibrant Red, to ensure your posters come to life. The ability to accurately reproduce clear text, and fine lines ensures the iPF6400SE is a versatile addition to your business.

The iPF6400SE will allow you to turn around your creative ideas in record time. You can create and replace your posters quickly and easily as many times as you want, with minimal cost. Always ensure your marketing remains relevant, fresh and always eye-catching.

At a glance

- 24 inch
- 2400 x 1200 dpi
- 6 colour LUCIA-EX ink
- A1 poster in 35 seconds*
- Borderless printing
- Media configuration tool plug-in
- Broad media selection

Request your free 30 day trial of PosterArtist today from wide-format@canon.com.au



High Capacity Ink Tanks

Optional 300ml ink tanks for greater productivity and less ink changes



“Hot” Swap

Change ink tanks without pausing your print job



PosterArtist Lite

Print multiple formats with a simple “drag and drop” process with our Direct Print & Share Utility



LUCIA EX ink system

LUCIA EX ink offers long-lasting prints, that resists fading over time



Accounting Manager

Software helps keep track of printing costs



Red Ink Tank

Ensure vivid reds and oranges with the included Red Ink tank

*Upgradable to PosterArtist

Canon

no one sees print like you

imagePROGRAF iPF6400SE

product specifications

MAIN UNIT

Print head	PF-05 (1 printhead installed)
Technology	FINE (Full-Photolithography Inkjet Nozzle Engineering)
Print Resolution (Max)	Up to 2400 × 1200 dpi
Ink Type	LUCIA EX Ink (Pigment-based)
Ink tank	130ml: PFI-106 BK/MBK/C/M/Y/R 300ml: PFI-206BK/MBK/C/M/Y/R
Colours	Black, Matte Black, Cyan, Magenta, Yellow, Red
Ink tank shipped with Printer	6 Colours (Full 90ml Each Colour)
Printer Memory	256 mb
Power supply	AC 100 - 240 V (50 - 60 Hz)
Power Consumption	Maximum 100W or Less Standby (100-120V) 5 W or Less Power Off 0.5W or Less (compliant with executive order)
Certifications	International Energy Star Program (WW), RoHS directive
Operation Environment	Temperature 15 – 30°C (59 – 86°F) Relative Humidity 10 – 80% (No Condensation)
Dimensions with Stand (HxWxD)	991 x 751 x 1017
Weight	54 kg
User replaceable items	Print-Head PF-05 Maintenance Cartridge MC-16

MEDIA SPECIFICATIONS

Media Feed	Auto Roll Feed Unit - One Roll - top loading front output Cut sheet Manual feed - front loading and front output Cut sheet Manual feed - top loading and front output
Media Width	8" (203.2mm) – 24" (609.6mm) (Cut Sheet and Roll) *Formal supported "Media Width" is limited to the "Media Size" (roll paper widths)
Minimum media Length	Roll Paper 203.2 mm Cut Sheet 279.4 mm
Maximum print length	Roll Paper 18 m (Varies according to the OS and application) Cut Sheet 1.6 m
Borderless printing widths (Roll Media only)	10" (254 mm), B4 (257 mm), 14" (356 mm), 16" (407 mm), A2 (420 mm), A2+1/17" (432 mm), B2 (515 mm), A1 (594 mm), 24" (610 mm)
Printer stand	Standard
Media Thickness	0.07mm - 0.8mm (Cut Sheet and Roll)
Media Cores Sizes	2" and 3" Core (Adapter Included)
Printable margins	Manual Feed (Top/Front) Leading and Left/Right Edges: 3mm (0.12") Trailing Edge, Front Feed: 23mm (0.90") Trailing Edge, Top Feed: 3mm (0.12") Except Art Paper 23mm (0.90") Roll Feed, All Sides: 3mm (0.12") or 0" for Borderless
Maximum media roll outer diameter	150 mm
Acoustic Noise	Operation 49dB or Less



SOFTWARE SPECIFICATIONS

Printer software	Canon Printer Driver, Print Plug-in for Photoshop, **Print Plug-in for DPP, ***Printer Driver Extra Kit (Free Layout, imageRUNNER Linking Function), Print Plug-in for Microsoft Office
Applications	PosterArtist Lite with Poster Solutions (PC only)
Utilities	imagePROGRAF Status Monitor (Windows), Print Monitor (Macintosh), Media Configuration Tool, Remote UI, Accounting Manager
Printer Language	GARO (Graphic Arts language with Raster Operations)
Operating systems	Windows XP (32/64-bit), Server 2003 (32/64-bit), Server 2008 (32/64-bit), Windows Vista™ (32/64-bit), Windows 7 (32/64-bit); Macintosh™ OS X 10.5.8 - 10.7.x
Interface	Standard USB 2.0 High-Speed 10/100/1000 Base - T/TX

OPTIONS/ACCESSORIES

Roll Holder Set RH2-25
STAND ST-29
PosterArtist (PC Only)

- * The maximum printable length varies depending on the application, OS, and RIP used. The maximum printable length from Canon Printer Driver is 50 feet.
- ** For Adobe Photoshop 6, 7, CS, CS2, CS3, CS4 running on Windows 2000/XP/Windows Vista (32 bit)/Windows 7 or Macintosh OS X 10.2/10.3/10.4/10.5/10.6.
- *** For Digital Photo Professional version 2.1 or later running on Windows 2000/XP/Windows Vista (32 bit)/Windows 7 or Macintosh OS X 10.2/10.3/10.4/10.5/10.6.
- ^ For imagePROGRAF Printer Driver. For printing from PostScript™ applications such as Adobe Illustrator™ or QuarkXPress™, please use a PostScript compatible RIP package. For a list of Canon recommended RIP packages, please consult with Canon Alliance and Industry Market program list of RIP vendors.



Australia: call 1800 444 199 or visit canon.com.au

New Zealand: call 0800 222 666 or visit canon.co.nz

